


LINNEA-ZT25

Asymmetric beam for wall washing and 1.0 mm metal sheet or profile



TECHNICAL SPECIFICATIONS:

Dimensions	285x40 mm
Height	11.6 mm
Fastening	clips
Colour	clear
Box size	578 x 378 x 295 mm
Box weight	7.1 kg
Quantity in Box	180 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
LINNEA-ZT25	Lens	PC	clear




PHOTOMETRIC DATA (MEASURED):




LED CALOSNU405-M7W1
FWHM Asymmetric
Efficiency 81 %
Peak intensity 0.760 cd/lm
Required components:




LED CALOSNU410-M7W1
FWHM Asymmetric
Efficiency 81 %
Peak intensity 0.750 cd/lm
Required components:



LED Tridino 1ft 1100lm xxxHE 1R HV
FWHM Asymmetric
Efficiency 79 %
Peak intensity 0.680 cd/lm
Required components:




LED XP-E
FWHM Asymmetric
Efficiency 80 %
Peak intensity 0.720 cd/lm
Required components:




PHOTOMETRIC DATA (MEASURED):




LED NFSx757G
 FWHM Asymmetric
 Efficiency 80 %
 Peak intensity 0.800 cd/lm
 Required components:




LED PrevaLED Linear Slim 3 (1100lm)
 FWHM Asymmetric
 Efficiency 80 %
 Peak intensity 0.790 cd/lm
 Required components:



LED PrevaLED Linear Slim 3 (2000lm)
 FWHM Asymmetric
 Efficiency 80 %
 Peak intensity 0.780 cd/lm
 Required components:




LED Duris S5 (2 chip)
 FWHM Asymmetric
 Efficiency 81 %
 Peak intensity 0.760 cd/lm
 Required components:



PHOTOMETRIC DATA (MEASURED):


OSRAM
Opto Semiconductors

LED Duris S5 (Single chip)
FWHM Asymmetric
Efficiency 83 %
Peak intensity 0.780 cd/lm
Required components:




PHILIPS

LED Fortimo LED Strip 1ft 1100lm FC HV4 & LV4
FWHM Asymmetric
Efficiency 81 %
Peak intensity 0.810 cd/lm
Required components:




PHILIPS

LED Fortimo LED Strip 1ft 650lm FC HV4 & LV4
FWHM Asymmetric
Efficiency 81 %
Peak intensity 0.760 cd/lm
Required components:



SAMSUNG


LED LM561B Plus
FWHM Asymmetric
Efficiency 79 %
Peak intensity 0.700 cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):


SAMSUNG

LED LT-H282C
FWHM Asymmetric
Efficiency 82 %
Peak intensity 0.680 cd/lm
Required components:




SAMSUNG

LED LT-H562C
FWHM Asymmetric
Efficiency 82 %
Peak intensity 0.680 cd/lm
Required components:




SAMSUNG

LED LT-Q282B
FWHM Asymmetric
Efficiency 82 %
Peak intensity 0.710 cd/lm
Required components:



SAMSUNG


LED LT-S282H
FWHM Asymmetric
Efficiency 81 %
Peak intensity 0.710 cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):


SAMSUNG

LED LT-S562H
FWHM Asymmetric
Efficiency 81 %
Peak intensity 0.710 cd/lm
Required components:




SAMSUNG

LED LT-V282E
FWHM Asymmetric
Efficiency 82 %
Peak intensity 0.730 cd/lm
Required components:




SAMSUNG

LED LT-V562E
FWHM Asymmetric
Efficiency 82 %
Peak intensity 0.730 cd/lm
Required components:








SEOUL SEMICONDUCTOR

LED SEOUL 5630D
FWHM Asymmetric
Efficiency 80 %
Peak intensity 0.720 cd/lm
Required components:




PHOTOMETRIC DATA (MEASURED):

<p> SEUL SEMICONDUCTOR</p> <p>LED SunLike 3030 FWHM Asymmetric Efficiency 82 % Peak intensity 0.800 cd/lm Required components:</p>	
<p>TRIDONIC</p> <p>LED LLE G4 24x280mm 1250lm FWHM Asymmetric Efficiency 82 % Peak intensity 0.800 cd/lm Required components:</p>	
<p>TRIDONIC</p> <p>LED LLE G4 24x280mm 2000lm ADV FWHM Asymmetric Efficiency 81 % Peak intensity 0.710 cd/lm Required components:</p>	
<p>TRIDONIC</p> <p>LED LLE G4 24x280mm 650lm FWHM Asymmetric Efficiency 82 % Peak intensity 0.840 cd/lm Required components:</p>	


PHOTOMETRIC DATA (SIMULATED):




LED XP-E
FWHM Asymmetric
Efficiency 84 %
Peak intensity 0.900 cd/lm
Required components:




LED XT-E
FWHM Asymmetric
Efficiency 81 %
Peak intensity 0.730 cd/lm
Required components:



LED LG 5630
FWHM Asymmetric
Efficiency 82 %
Peak intensity 0.650 cd/lm
Required components:




LED LUXEON 3030 2D (Round LES)
FWHM Asymmetric
Efficiency 83 %
Peak intensity 0.850 cd/lm
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED NF2x757G
FWHM Asymmetric
Efficiency 84 %
Peak intensity 0.790 cd/lm
Required components:




LED NFSx757D
FWHM Asymmetric
Efficiency 73 %
Peak intensity 0.000 cd/lm
Required components:



LED Duris E5
FWHM Asymmetric
Efficiency 82 %
Peak intensity 0.740 cd/lm
Required components:



LED LM561B
FWHM Asymmetric
Efficiency 73 %
Peak intensity 0.000 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)